




# It's Fendt. Because we understand Agriculture.











fendt.com | Fendt is a worldwide brand of AGCO.

Cutter drum mower bed	Working width (m)	Cutting drums/Blades per cutting drum (number)	Power requirement (kW/HP)
 2940 FPV	2,86	4 / 3	55/75
3140 FPV	3,06	4 / 3	55/75
3340 FPV	3,26	4 / 3	55/75
 310 TL	3,06	4 / 3	60/82

Slicer disc mower bed	Working width (m)	Cutting discs/Blades per cutting disc (number)	Power requirement (kW/HP)
 260 FP <b>ALPIN</b>	2,50	4 / 2	28/38
260 FPS <b>ALPIN</b>	2,50	4 / 2	28/38
 310 FPK <b>ALPIN</b>	3,00	6 / 2	55/75
 310 F	3,10	6 / 2	44/60
310 F KC	3,10	6 / 2	55/75
310 F RC	3,10	6 / 2	52/70
310 FQ	3,10	6 / 2	44/60
310 FQ KC	3,10	6 / 2	56/75
310 FQ RC	3,10	6 / 2	52/70
360 FQ	3,60	7 / 2	52/70
360 FQ KC	3,60	7 / 2	67/90
360 FQ RC	3,60	7 / 2	63/85
 2460 ISL	2,42	6 / 2	37/50
2870 ISL	2,82	7 / 2	44/60
270 P	2,55	5 / 2	40/54
320 P	3,00	6 / 2	45/61
350 P	3,50	7 / 2	50/68
 4080 TL	4,00	8 / 2	72/99
4590 TL	4,50	9 / 2	84/115
 3160 TLX	3,10	6 / 2	63/85
3160 TLXKC	3,10	6 / 2	85/115
3160 TLXRC	3,10	6 / 2	85/115
3670 TLX	3,60	7 / 2	70/95
3670 TLXKC	3,60	7 / 2	96/130
3670 TLXRC	3,60	7 / 2	96/130
 860	8,30/8,60	2 x 6 / 2	81/110
860 KC	8,30/8,60	2 x 6 / 2	110/150
860 RC	8,30/8,60	2 x 6 / 2	103/140
960	9,30/9,60	2 x 7 / 2	96/130
991 TLKC	9,30	2 x 7 / 2	155/200
 9314 TLKCB	9,30	2 x 7 / 2	168/228
 313 TKC	3,00	6 / 2	66/90
313 TRC	3,00	6 / 2	66/90

Lotus tedder	Working width (m)	Rotor/Tine arms per rotor (number)	Power requirement (kW/HP)
 770	7,70	6 / 6	55/75
1020 T	10,20	8 / 7	44/60
1250 T	12,50	10 / 7	70/95


Twister tedder	Working width (m)	Rotor/Tine arms per rotor (number)	Power requirement (kW/HP)
 431 DN <b>ALPIN</b>	4,30	4 / 6	22/30
601 DN <b>ALPIN</b>	5,70	6 / 5	25/34
 5204 DN	5,20	4 / 6	22/30
6606 DN	6,60	6 / 6	30/41
7706 DN	7,70	6 / 6	60/82
8608 DN	8,60	8 / 6	70/95
11010 DN	10,70	10 / 6	88/120
 901 T	8,60	8 / 6	40/54
11008 T	10,20	8 / 6	40/54
13010 T	12,70	10 / 6	66/90





Former rake	Working width (m)	Rotor/Tine arms per rotor (number)	Power requirement (kW/HP)
 351 DS <b>ALPIN</b>	3,60	1 / 10	25/34
351 DN	3,60	1 / 10	20/27
391 DN	3,80	1 / 10	20/27
400 DN	3,85	1 / 10	20/27
426 DN	4,20	1 / 12	30/41
456 DN	4,50	1 / 12	30/41
 1502	6,30 / 7,00	2 / 12 / 12	33/45
 1402	5,75 / 6,65	2 / 10 / 12	19/26
1452	5,80 / 6,70	2 / 12 / 12	19/26
1603	6,60 / 7,70	2 / 12 / 12	30/41
7850	7,80 / 8,40	2 / 13 / 13	44/60
7850 PRO	7,80 / 8,40	2 / 13 / 13	44/60
 671	5,80 - 6,60	2 / 10 / 10	19/26
801	6,80 - 7,60	2 / 12 / 12	30/41
880	7,20 - 8,00	2 / 12 / 12	35/48
8055 PRO	7,20 - 8,00	2 / 12 / 12	35/48
10065	8,80 - 10,00	2 / 15 / 15	51/70
10065 PRO	8,80 - 10,00	2 / 15 / 15	51/70
 12545	10,60 - 12,50	4 / 4 x 12	59/80
12545 PRO	10,60 - 12,50	4 / 4 x 12	59/80
14055 PRO	10,50 - 13,80	4 / 4 x 13	96/130



**Forage harvesting solutions:**

- B = Cross conveyor belt
- DN = Three-point hitch with trailing device
- DS = Three-point hitch rigid
- F/FP = Front-mounted pendulum support
- FPK = Front-mounted pendulum support – short
- FQ = Front attachment 3D drawbar
- ISL = Spur gear drive inner shoeless
- KC = Tine conditioner
- P = Paired direction of rotation
- RC = Roller conditioner
- S = Side shift
- T = Transport chassis frame
- TL = TurboLift system, number of required hydraulic connections may vary depending on optional equipment
- V = Cutting height adjustment
- X = X-Transport position

Not all models available in all markets.

Large Square Balers	Dimension Width x Height (cm)	Axle/Cutter	Power requirement (kW/HP)
 990 SP	80 x 90	Single/No	112/150
990 TP	80 x 90	Tandem/No	112/150
990 TC	80 x 90	Tandem/Yes	135/180
1270 SP	120 x 70	Single/No	120/160
1270 TP	120 x 70	Tandem/No	120/160
1270 TC	120 x 70	Tandem/Yes	142/190
1290 SP	120 x 90	Single/No	127/170
1290 TP	120 x 90	Tandem/No	127/170
1290 TC	120 x 90	Tandem/Yes	149/200
1290 XD TP	120 x 90	Tandem/No	149/200
1290 XD TC	120 x 90	Tandem/Yes	186/250
12130 SP	120 x 130	Single/No	150/200
12130 TP	120 x 130	Tandem/No	150/200

Rotana round balers	Baler chamber volume (m³)	Baler chamber diameter (m)	Power requirement (kW/HP)
 130 F	1,50	1,25	45/60
130 F Xtra	1,50	1,25	60/80
 130 F Combi	1,50	1,25	100/140
 160 V	2,50	0,70 - 1,60	55/80
160 V Xtra	2,50	0,70 - 1,60	55/80
180 V	3,10	0,70 - 1,80	70/110
180 V Xtra	3,10	0,70 - 1,80	70/110
 160 V Combi	2,50	0,90 - 1,60	100/140

Roller round bale wrapper	Bale diameter (m)	Overall width (m)	Power requirement (kW/HP)
 130	0,90 - 1,30	2,55	30/40
 160	1,25-1,50	2,30	40/55

**Square balers:**

- C = Cutter
- P = Packer
- S = Single axle
- T = Tandem axle
- XD = High compaction



**Balers:**




- Combi = Wrapper combination
- F = Fixed chamber
- V = Variable chamber
- Xtra = Cutter

**Forage Wagon:**

- R = Rotor
- S = Swingarm

Tigo forage wagons	Volumes in accordance with DIN 11741 (m³)	Power requirement (kW/HP)
 35 ST	22	29/40
40 ST	24,5	44/60
50 ST	29	51/70
 35 S	22	29/40
40 S	24,5	44/60
50 S	29	51/70
 40 MS	26	59/80
50 MS	30	63/85
60 MS	35	70/95
70 MS	39	81/110
 40 MR	26	66/90
50 MR	30	74/100
60 MR	35	88/120
 50 MR Profi	31	74/100
60 MR Profi	36	88/120
100 MR Profi	50	88/120
 45 PR	31	96/130
50 PR	31	96/130
60 PR	36	110/150
 65 VR	37	110/150
75 VR	42,5	110/150
 65 XR	38	132/180
75 XR	44	147/200
90 XR	50	169/230
100 XR	54	184/250

Katana forage harvester	Engine horsepower (ECE R 120) (kW/hp)
 Katana 650	478/650
 Katana 850	623/847

Katana attachments	Working width (m)	Number of Axles
 360 <sup>plus</sup>	6,00	8
375 <sup>plus</sup>	7,50	10
390 <sup>plus</sup>	9,00	12
 460 <sup>plus</sup>	6,00	4
460 <sup>plus</sup> Stalkbuster	6,00	4
475 <sup>plus</sup>	7,50	6
490 <sup>plus</sup>	9,00	6
 Gras-Pick-UP 3003	3,00	-